



Quality Paints since 1845  
**MATHYS®**



## AMW FUNGICIDAL WASH

# Effective algae, fungi and dirt remover

- Removes and prevents growth from fungi and algae
- HSE approved biocide
- Ready-mix product
- Does not harm glass or PVC
- For bituminous substrates, concrete, masonry, plaster and woodwork



# AMW FUNGICIDAL WASH

## POPIS PRODUKTU (DLOUHÝ)

Ready-mix fungi and algae remover for walls and roofs.

## DOPORUČENÉ POUŽITÍ

As a masonry surface fungicidal wash for professional use against mould, fungi, moss, etc. Also suitable for treatment of similarly affected roof surfaces.

## TEORETICKÁ SPOTŘEBA

5 m<sup>2</sup>/l

## PRAKTICKÁ SPOTŘEBA

Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

## PŘÍPRAVA POVRCHU

All mould, fungi, lichens etc. should be given a saturated coat of AMW before their complete removal (to kill spores). Remove debris by power washing or use of a stiff brush. The whole area should then be given a second coat of AMW and allowed to dry (to render the substrate sterile).

## NÁVOD K POUŽITÍ

Apply AMW abundantly, preferably by brush, and wait 12 hours. Dry-brush and remove dust prior to painting, or clean with high-pressure water and let the surface dry. Affected by heavy rainfall for at least 4 hours after application. If doubtful re-apply. Ensure residues are substantially diluted with water before entering drains etc.

## PODMÍNKY POUŽITÍ

Minimum 8°C and maximum 80% R.H.

## APLIKACE A ŘEDĚNÍ: ŠTĚTEC

Do not dilute.

## APLIKACE A ŘEDĚNÍ: VZDUCHOVÝ ATOMIZOVANÝ SPREJ

"Coarse" spray such as a pneumatic garden spray. Do not dilute.

## ČIŠTĚNÍ ZAŘÍZENÍ / ROZLITÍ

Water.

## POZNÁMKY

This fungicidal product is only available in the UK, so not available for Export. HSE-approval no. 9225

## DATA SAFETY DATA

Úroveň těkavých organických

látek:

0 g/l

Poznámky k bezpečnosti:

Consult Safety Data Sheet and Safety Information printed on the can.

Use biocides safely. Always read the label and product information before use.

## PH

4,50

## DOBA POUŽITELNOSTI

Minimum of 3 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C. **Protect material from frost.**

last\_updated: 07/02/2025

footer\_data\_colors\_pack\_sizes: footer\_data\_colors\_pack\_sizes.value

footer\_data\_disclaimer: footer\_data\_disclaimer.value

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
info@rust-oleum.eu

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
info@rust-oleum.eu

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
info@rust-oleum.eu

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
info@rust-oleum.eu