



Quality Paints since 1845
MATHYS®



AMW FUNGICIDAL WASH

Effective algae, fungi and dirt remover

- Removes and prevents growth from fungi and algae
- HSE approved biocide
- Ready-mix product
- Does not harm glass or PVC
- For bituminous substrates, concrete, masonry, plaster and woodwork

AMW FUNGICIDAL WASH

POPIS PRODUKTU (DLHÝ)

Ready-mix fungi and algae remover for walls and roofs.

ODPORÚČANÉ POUŽITIE

As a masonry surface fungicidal wash for professional use against mould, fungi, moss, etc. Also suitable for treatment of similarly affected roof surfaces.

TEORETICKÁ SPOTREBA

5 m²/l

PRAKTICKÁ VÝDATNOSŤ

Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

PRÍPRAVA POVRCHU

All mould, fungi, lichens etc. should be given a saturated coat of AMW before their complete removal (to kill spores). Remove debris by power washing or use of a stiff brush. The whole area should then be given a second coat of AMW and allowed to dry (to render the substrate sterile).

NÁVOD NA POUŽITIE

Apply AMW abundantly, preferably by brush, and wait 12 hours. Dry-brush and remove dust prior to painting, or clean with high-pressure water and let the surface dry. Affected by heavy rainfall for at least 4 hours after application. If doubtful re-apply. Ensure residues are substantially diluted with water before entering drains etc.

PODMIENKY APLIKÁCIE

Minimum 8°C and maximum 80% R.H.

APLIKÁCIA A RIEDENIE: ŠTETEC

Do not dilute.

APLIKÁCIA A RIEDENIE: VZDUCHOVO ATOMIZOVANÝ SPREJ

"Coarse" spray such as a pneumatic garden spray. Do not dilute.

ČISTENIE ZARIADENIA / POSTRIEKANIE

Water.

POZNÁMKY

This fungicidal product is only available in the UK, so not available for Export. HSE-approval no. 9225

DATA SAFETY DATA

Úroveň VOC: 0 g/l
Poznámky k bezpečnosti: Consult Safety Data Sheet and Safety Information printed on the can.
Use biocides safely. Always read the label and product information before use.

PH

4,50

SKLADOVATELNOSŤ

Minimum of 3 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C. **Protect material from frost.**

last_updated: 07/02/2025

footer_data_colors_pack_sizes: footer_data_colors_pack_sizes.value

footer_data_disclaimer: footer_data_disclaimer.value

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu