

Quality Paints since 1845
MATHYS[®]



DIVALO

Varnish for the finishing touch of interior wall paints.

- Not yellowing
- Smooth satin views
- Washable

DIVALO

POPIS PRODUKTU (DLOUHÝ)

Water based acrylic varnish. For the finishing touch of interior wall paints when a high mechanical resistance is required.

DOPORUČENÉ POUŽITÍ

Finish on indoor paints and decorative paint systems when a high mechanical resistance is required. Recommended as a topcoat on decorative paint systems (Fair-Decor).

TECHNICAL DATA

Hustota (g/cm ³):	1,02 - 1,06
Úroveň lesku:	Satin
Úroveň lesku při 60°:	Satin Gloss: ± 20%
Obsah pevných látek v hmotnosti:	30 - 33 %
Obsah pevných látek v objemu:	27,5 - 30,5 %

DRY TIMES BY 20

Dotykem suché:	30 minutes
Suchý nátěr:	4 hours
Plně vytvrzené:	± 1 week

DOPORUČENÁ TLOUŠŤKA MOKRÉHO FILMU

± 70 µm

DOPORUČENÁ TLOUŠŤKA SUCHÉHO FILMU

± 20 µm

TEORETICKÁ SPOTŘEBA

12 - 14 m²/l

PRAKTICKÁ SPOTŘEBA

Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

PŘÍPRAVA POVRCHU

Clean and degrease substrate. The paint coats or systems that have to be protected have to be dry and/or fully cured.

NÁVOD K POUŽITÍ

To ensure homogeneity, coating materials should be thoroughly stirred prior to use.

PODMÍNKY POUŽITÍ

> 5°C, max. 80% R.H.

APLIKACE A ŘEDĚNÍ: ŠTĚTEC

Apply in 1 or 2 coats with flat brush. If necessary dilute with water.

APLIKACE A ŘEDĚNÍ: VÁLEČEK

Apply in 1 or 2 coats with lacquer. If necessary dilute with water.

APLIKACE A ŘEDĚNÍ: BEZVZDUCHOVÝ SPREJ

Nozzle: 09 - 013 / Pressure: 180 bars.

APLIKACE A ŘEDĚNÍ: VZDUCHOVÝ ATOMIZOVANÝ SPREJ

If necessary dilute with water.

ČIŠTĚNÍ ZAŘÍZENÍ / ROZLITÍ

Water.

DATA SAFETY DATA

Úroveň těkavých organických látek:	90 g/l
VOC readymix:	90 g/l
Kategorie VOC:	A/e
Limitní hodnota VOC:	130 g/l
Grenelle:	A+
Poznámky k bezpečnosti:	Consult Safety Data Sheet and Safety Information printed on the can.

DOBA POUŽITELNOSTI

Minimum of 2 years from date of production in unopened cans. If stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

last_updated: 07/02/2025

footer_data_colors_pack_sizes: footer_data_colors_pack_sizes.value

footer_data_disclaimer: footer_data_disclaimer.value

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu