



Quality Paints since 1845
MATHYS[®]



FASSICRYL PRIMER

Water-based primer

- Superb adhesion
- Perfect flow viscosity
- Good coverage
- Easy to apply



FASSICRYL PRIMER

POPIS PRODUKTU (DLOUHÝ)

Fassicryl Primer is a water-based primer with excellent adhesion, for indoor and outdoor use. Based on an acrylic dispersion and PU-Alkyd emulsion. Fast-drying adhesive primer with perfect flow viscosity. Suitable as a primer for various wood types and properly cleaned paint layers with good adhesion. Can also be applied to plastic and non-ferrous metals.

DOPORUČENÉ POUŽITÍ

Primer for application to various wood types before painting and properly cleaned old paint layers with good adhesion.

DOPORUČENÝ SYSTÉM

Priming a surface with Fassicryl Primer. Use Fassicryl Sealing Primer on bleeding wood types. Finish with a Fassicryl lacquer.

TECHNICAL DATA

Hustota (g/cm³): 1,35 (white - wit - blanc - weiß)
Úroveň lesku: Matt
Obsah pevných látek v objemu: 38% (white - wit - blanc - weiß)

DRY TIMES BY 20

Dotykem suché: 1 hour
Suchý nátěr: 6 hours

DOPORUČENÁ TLOUŠŤKA MOKRÉHO FILMU

80 µm (white - wit - blanc - weiß)

DOPORUČENÁ TLOUŠŤKA SUCHÉHO FILMU

30 µm (white - wit - blanc - weiß)

TEORETICKÁ SPOTŘEBA

12-14 m²/l/coat

PRAKTICKÁ SPOTŘEBA

Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

PŘÍPRAVA POVRCHU

The surface must be dry and free of dust and grease.

Aged wood: remove until the healthy wood is exposed.

Exposed wood: degrease (Multi Cleaner), sand and remove all dust.

Old paint layers in a poor condition: strip (NR.1 GREEN PAINT STRIPPER), degrease (Multi Cleaner), sand, remove all dust and prime.

Old paint layers in a good condition: degrease (Multi Cleaner), sand and remove all dust.

Round off sharp edges so that you can apply a good coating.

NÁVOD K POUŽITÍ

The product must be firmly stirred into a homogeneous substance prior to its use. Use a suitable brush or roller to apply one or two coats.

PODMÍNKY POUŽITÍ

> 8°C, < 80% R.H.

APLIKACE A ŘEDĚNÍ: ŠTĚTEC

Apply undiluted with brush with synthetic bristles.

APLIKACE A ŘEDĚNÍ: VÁLEČEK

Apply undiluted with a 10 mm micro fiber roller.

ČIŠTĚNÍ ZAŘÍZENÍ / ROZLITÍ

Clean the material with water and dispose of the residue appropriately.

POZNÁMKY

Do not apply paint at temperatures below 8°C. The surface temperature must be at least 3°C above the dew point.

DATA SAFETY DATA

Úroveň těkavých organických

látek: 50g/l

VOC readymix: 50g/l

Kategorie VOC: IIA/d

Limitní hodnota VOC: 130g/l

Poznámky k bezpečnosti: Consult Safety Data Sheet and Safety Information printed on the can.

DOBA POUŽITELNOSTI

Minimum of 2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5 and 35°C.

last_updated: 07/02/2025

footer_data_colors_pack_sizes: footer_data_colors_pack_sizes.value

footer_data_disclaimer: footer_data_disclaimer.value

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chiène
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu