



Quality Paints since 1845  
**MATHYS**<sup>®</sup>



## **FASSICRYL PRIMER**

### **Water-based primer**

- Superb adhesion
- Perfect flow viscosity
- Good coverage
- Easy to apply



# FASSICRYL PRIMER

## POPIS PRODUKTU (DLHÝ)

Fassicryl Primer is a water-based primer with excellent adhesion, for indoor and outdoor use. Based on an acrylic dispersion and PU-Alkyd emulsion. Fast-drying adhesive primer with perfect flow viscosity. Suitable as a primer for various wood types and properly cleaned paint layers with good adhesion. Can also be applied to plastic and non-ferrous metals.

## ODPORÚČANÉ POUŽITIE

Primer for application to various wood types before painting and properly cleaned old paint layers with good adhesion.

## ODPORÚČANÝ SYSTÉM

Priming a surface with Fassicryl Primer. Use Fassicryl Sealing Primer on bleeding wood types. Finish with a Fassicryl lacquer.

## TECHNICAL DATA

Hustota (g/cm<sup>3</sup>): 1,35 (white - wit - blanc - weiß)  
Úroveň lesku: Matt  
Obsah pevných látok v objeme: 38% (white - wit - blanc - weiß)

## DRY TIMES BY 20

Na dotyk suché: 1 hour  
Suchý na opätovné natieranie: 6 hours

## ODPORÚČANÁ HRúbKA MOKRÉHO FILMU

80 µm (white - wit - blanc - weiß)

## ODPORÚČANÁ HRúbKA SUCHÉHO FILMU

30 µm (white - wit - blanc - weiß)

## TEORETICKÁ SPOTREBA

12-14 m<sup>2</sup>/l/coat

## PRAKTICKÁ VÝDATNOSŤ

Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

## PRÍPRAVA POVRCHU

The surface must be dry and free of dust and grease.

Aged wood: remove until the healthy wood is exposed.

Exposed wood: degrease (Multi Cleaner), sand and remove all dust.

Old paint layers in a poor condition: strip (NR.1 GREEN PAINT STRIPPER), degrease (Multi Cleaner), sand, remove all dust and prime.

Old paint layers in a good condition: degrease (Multi Cleaner), sand and remove all dust.

Round off sharp edges so that you can apply a good coating.

## NÁVOD NA POUŽITIE

The product must be firmly stirred into a homogeneous substance prior to its use. Use a suitable brush or roller to apply one or two coats.

## PODMIENKY APLIKÁCIE

> 8°C, < 80% R.H.

## APLIKÁCIA A RIEDENIE: ŠTETEC

Apply undiluted with brush with synthetic bristles.

## APLIKÁCIA A RIEDENIE: VALEC

Apply undiluted with a 10 mm micro fiber roller.

## ČISTENIE ZARIADENIA / POSTRIEKANIE

Clean the material with water and dispose of the residue appropriately.

## POZNÁMKY

Do not apply paint at temperatures below 8°C. The surface temperature must be at least 3°C above the dew point.

## DATA SAFETY DATA

Úroveň VOC: 50g/l  
VOC readymix: 50g/l  
Kategória VOC: IIA/d  
Limit VOC: 130g/l  
Poznámky k bezpečnosti: Consult Safety Data Sheet and Safety Information printed on the can.

## SKLADOVATEĽNOSŤ

Minimum of 2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5 and 35°C.

last\_updated: 07/02/2025

footer\_data\_colors\_pack\_sizes: footer\_data\_colors\_pack\_sizes.value

footer\_data\_disclaimer: footer\_data\_disclaimer.value

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T: +31 (0) 165 593 636  
F: +31 (0) 165 593 600  
info@rust-oleum.eu

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T: +44 (0)1914 113 146  
F: +44 (0)1914 113 147  
info@rust-oleum.eu

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chiène  
95322 Herblay  
France  
T: +33(0) 130 40 00 44  
F: +33(0) 130 40 99 80  
info@rust-oleum.eu

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T: +32 (0) 13 460 200  
F: +32 (0) 13 460 201  
info@rust-oleum.eu