



PARACEM[®] DECO SOFT

High-quality semi-matt interior wall paint

- Excellent flow
- Good mechanical resistance against rubbing
- Smooth semi-matt aspect
- Closed coating structure, washable
- High covering power

PARACEM® DECO SOFT

POPIS PRODUKTU (DLHÝ)

Paracem® Deco Soft is a waterborne acrylic paint for interior application.

ODPORÚČANÉ POUŽITIE

Decorative and satin matt finishing for indoor walls and ceilings.
Applicable on most substrates (plaster, bricks, concrete, etc.) as well on glass fibre.

TECHNICAL_DATA

Hustota (g/cm ³):	1,33 - 1,37 (white - wit - blanc)
Úroveň lesku:	Matt,Semi-Matt
Úroveň lesku pri 60°:	Satin matt: 5-8%
Úroveň lesku pri 85°:	Satin matt: 15-20%
Obsah pevných látok v hmotnosti:	52 - 54% (white - wit - blanc)
Obsah pevných látok v objeme:	38 - 40% white - wit - blanc)
Odolnosť voči mokrému drhnutiu (EN 13300):	wsr_c1

DRY_TIMES_BY_20

Na dotyk suché:	1 hour
Suchý na opätovné natieranie:	2 hours
Úplne vytvrdnuté:	2 days

ODPORÚČANÁ HRúbKA MOKRÉHO FILMU

140 µm

ODPORÚČANÁ HRúbKA SUCHÉHO FILMU

55 µm

TEORETICKÁ SPOTREBA

7 - 9 m²/l per coat

PRAKTICKÁ VÝDATNOSŤ

Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

PRÍPRAVA POVRCHU

The surface must be dry and free of dust and grease.
You can paint Paracem® Deco Soft directly over clean, old layers of paint that are still in good condition and onto surfaces that are not too porous.
You must treat porous surfaces with Paracem® Deco Primer first.
Highly porous surfaces, smooth plaster, and water-resistant plasterboard must be impregnated with Pegafix first.
Nicotine and water stains must be isolated first with Pegamat® RL or Zinsser primers Bulls Eye 123 or 123 Plus.
Unpainted woodwork must be treated appropriately first and a priming coat must be applied (e.g. Fassiprim Aqua or Zinsser primers Bulls Eye 123 or 123 Plus).
Metal objects without rust spots are to be pre-treated with Pegalink®, or Zinsser primers Bulls Eye 123.
On glass fibre, apply preferably first a coat of Paracem® Deco Primer or Zinsser primers Bulls Eye 123 or 123 Plus before finishing with 2 coats of Paracem® Deco Soft.

NÁVOD NA POUŽITIE

To ensure homogeneity, coating materials should be thoroughly stirred prior to use.

PODMIENKY APLIKÁCIE

> 5°C, < 80% R.H.

APLIKÁCIA A RIEDENIE: ŠTETEC

Apply undiluted.

APLIKÁCIA A RIEDENIE: VALEC

Apply undiluted.

APLIKÁCIA A RIEDENIE: BEZVZDUCHOVÉ STRIEKANIE

Nozzle: 013 - 019 / Pressure: 160 - 200 bars.

APLIKÁCIA A RIEDENIE: VZDUCHOVO ATOMIZOVANÝ SPREJ

If required dilute with water.

ČISTENIE ZARIADENIA / POSTRIEKANIE

Water.

DATA_SAFETY_DATA

Úroveň VOC:	14 g/l
VOC readymix:	30 g/l
Kategória VOC:	A/a
Limit VOC:	30 g/l
Poznámky k bezpečnosti:	Consult Safety Data Sheet and Safety Information printed on the can.

SKLADOVATELNOSŤ

Minimum of 2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

last_updated: 07/02/2025

footer_data_colors_pack_sizes: footer_data_colors_pack_sizes.value

footer_data_disclaimer: footer_data_disclaimer.value

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu