

Quality Paints since 1845  
**MATHYS**<sup>®</sup>



## PARACEM<sup>®</sup> DECO ULTRA CLEAN XTRA MATT

### Excellent washable, extra-matt interior paint

- Excellent washability - Scrub resistance class 1
- Not glossy
- Limited writing effect in dark colors
- Good coverage
- Excellent flow

# PARACEM® DECO ULTRA CLEAN XTRA MATT

## BESKRIVELSE

Paracem® Deco Ultra Clean Xtra Matt is a highly washable alkaline emulsion, water-based interior wall paint with a lasting extra matt aspect. This decorative paint is available in white and in almost all possible colours, ranging from light to dark shades.

## ANBEFALT BRUK

It's perfect for interior walls that need regular cleaning (e.g. children's rooms, kitchens, etc.). Suitable for most substrates (plaster, brick, concrete, etc.) in public and private buildings. No 'white marking' occurs with darker colours.

## TEKNISKE DATA

|                            |                                  |
|----------------------------|----------------------------------|
| Tetthet:                   | 1,5 (white - wit - blanc - weiß) |
| Glansgrad:                 | extra_matt                       |
| Glansgrad ved 85°:         | Matt: 1%                         |
| Tørrestoffinnhold i volum: | 43% (white - wit - blanc - weiß) |
| wet_scrub_resistance:      | wsr_c1                           |

## TØRKETID VED 20°C/50% RELATIV LUFTFUKTIGHET

|             |         |
|-------------|---------|
| Støvtør:    | 2 hours |
| Håndterbar: | 2 hours |
| Overmalbar: | 6 hours |
| Herdetid:   | 30 days |

## ANBEFALT VÅTFILMYKKELSE

123 µm (white)

## ANBEFALT TØRRFILMYKKELSE

53 µm (white)

## TEORETISK FORBRUK

8 m<sup>2</sup>/l/coat

## PRAKTISK FORBRUK

Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

## KLARGJØRING AV OVERFLATE

The surface must be dry and free of dust and grease.

You can paint Paracem® Deco Ultra Clean Xtra Matt directly over clean, old layers of paint that are still in good condition and onto surfaces that are not too porous.

You must treat porous surfaces with Paracem® Deco Primer first.

Highly porous surfaces, smooth plaster, and water-resistant plasterboard must be impregnated with Pegafix first.

Nicotine and water stains must be isolated first with Pegamat® RL or Zinsser primers Bulls Eye 123 or 123 Plus.

Unpainted woodwork must be treated appropriately first and a priming coat must be applied (e.g. Fassiprim Aqua or Zinsser primers Bulls Eye 123 or 123 Plus).

Metal objects without rust spots are to be pre-treated with Pegalink®, or Zinsser primers Bulls Eye 123.

On glass fibre, apply preferably first a coat of Paracem® Deco Primer or Zinsser primers Bulls Eye 123 or 123 Plus before finishing with 2 coats of Paracem® Deco Ultra Clean Xtra Matt.

When working in combination with a joint sealant, we recommend using our acrylic sealant Elastopro, which can be painted over after drying for at least 1 hour (20°C, 60% r.h.).

## BRUKSANVISNING

To ensure homogeneity, thoroughly stir prior to use.

## PÅFØRINGSBETINGELSER

> 8°C, < 80% R.H.

## PÅFØRING & FORTYNNING: PENSEL

Apply undiluted with brush with synthetic bristles.

## PÅFØRING & FORTYNNING: RULLE

Apply undiluted with a 10 mm micro fiber roller.

## PÅFØRING & FORTYNNING: LUFTFRI SPRØYTE

Nozzle: 0.017 - 0.021 / Pressure: 180 bars. Spraying is only recommended for white and colours from base P.

## RENGJØRING AV UTSTYR/SPILL

Clean the material with water and dispose of the residue appropriately.

## MERKNADER

Do not apply at temperatures below +8°C.

Not recommended for use in damp rooms (eg bathrooms).

Cleaning instructions: Remove the contamination as soon as possible. Most contamination can easily be removed with a soft, damp cloth. Use lukewarm water and a mild colourless detergent. Do not use abrasive cleaning products. Do not use excessive pressure when cleaning as this may result in removing paint which will leave marks.

For more serious contaminations first wipe the substrate with a soft damp cloth, then use Mathys Multi-cleaner (diluted 1:100). Allow to dry.

The best cleaning results are achieved after the Paracem® Deco Ultra Clean Xtra Matt has dried for minimum 30 days.

Although extensive evaluations have been undertaken to ensure the cleanability of the Paracem® Deco Ultra Clean Xtra Matt it might be possible that some contamination is difficult to remove and leaves traces.

Touching the paint may leave marks this is due to the matt nature of the product (the marks will be more visible on dark colours). There may be a shiny effect after drying of the first coats in colours that are made of D and TR bases.

## SIKKERHETSDATA

|                    |        |
|--------------------|--------|
| VOC nivå:          | 10 g/l |
| VOC ferdigblandet: | 10 g/l |
| VOC kategori:      | IIA/a  |
| VOC grense:        | 30 g/l |

Merknader angående sikkerhet: Consult Safety Data Sheet and Safety Information printed on the can.

## HOLDBARHET

Minimum of 2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5 and 35°C.

Utstedt dato: 07/02/2025

**Tilgjengelige farger & størrelse på forpakninger:** Vennligst referer til den respektive produktsiden på [www.rust-oleum.eu](http://www.rust-oleum.eu) for en oversikt over tilgjengelige farger og størrelse på forpakninger.

**Ansvarsfraskrivelse:** Så langt vi kjenner til er informasjonen i dette dokumentet korrekt og nøyaktig. Den er gitt i god tro, men uten garanti. Brukeren må selv avgjøre om våre produkter er egnet for hans/hennes bestemte formål. Ikke under noen omstendigheter skal Rust-Oleum Europe bli gjort ansvarlig for indirekte eller tilfældige skader. Produktene må lagres, håndteres og påføres under forhold som tilfredsstillende Rust-Oleum Europes anbefalinger som er detaljert beskrevet i den siste oppdaterte kopien av produktdatabladet. Brukeren er selv ansvarlig for at de har den siste oppdaterte kopien. De siste oppdaterte kopier av produktdatabladet er tilgjengelig, og kan lastes ned gratis fra [www.rust-oleum.eu](http://www.rust-oleum.eu), eller de kan fås ved forespørsel til vår kundeserviceavdeling. Rust-Oleum Europe forbeholder seg retten til å endre egenskapene til produktene sine uten forhåndsvarsel.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T: +31 (0) 165 593 636  
F: +31 (0) 165 593 600  
info@rust-oleum.eu

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T: +44 (0)1914 113 146  
F: +44 (0)1914 113 147  
info@rust-oleum.eu

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T: +33(0) 130 40 00 44  
F: +33(0) 130 40 99 80  
info@rust-oleum.eu

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T: +32 (0) 13 460 200  
F: +32 (0) 13 460 201  
info@rust-oleum.eu