



PARACEM[®] UNIVERSAL

Excellent covering universal paint for all outside work

- Matt universal paint for the outdoors
- Usable on all surfaces, such as bricks, gutters, wood, aluminium, etc.
- Colour and weatherproof for long-term protection
- Protection of the dried coat against contamination by mould
- Primer and finishing coat in one



PARACEM® UNIVERSAL

POPIS PRODUKTU (DLOUHÝ)

Excellent covering universal paint for outside work. Extremely suitable for durable decoration of woodwork, metal, bricks, plastic, concrete and more. New or already painted. Paracem® Universal is water-vapour permeable, water repellent, and requires minimum maintenance. Self-priming in most cases. Protects dry coating against contamination by mould. Paracem® Universal has a unique property, namely, the colour does not darken when the façade is wet.

DOPORUČENÉ POUŽITÍ

Developed for all outside work, Paracem® Universal is ideal for applying to bricks, façade cladding, plaster, woodwork, plastic, galvanised metal, steel, concrete, and more. Paracem® Universal is self-priming and will immediately adhere to existing glossy surfaces without the need for sanding. A separate primer is unnecessary for most applications. Paracem® Universal provides excellent resistance against cracking, blistering, flaking, rain, and severe weather conditions. Two-layer system: Apply the first layer, which primes and seals the surface. The second layer completes the sealing process and provides additional moisture resistance and protection.

TECHNICAL DATA

Hustota (g/cm ³):	1,25
Úroveň lesku:	Matt
Úroveň lesku při 60°:	± 2%
Úroveň lesku při 85°:	± 3%
Obsah pevných látek v hmotnosti:	40%
Obsah pevných látek v objemu:	40%
Propustnost pro vodní páru:	Sd = 0,41 m

DRY TIMES BY 20

Dotykem suché:	1 h
Suché na manipulaci:	1 h
Suchý nátěr:	1 h
Plně vytvrzené:	7 days

DOPORUČENÁ TLOUŠŤKA MOKRÉHO FILMU

100 µm per coat

DOPORUČENÁ TLOUŠŤKA SUCHÉHO FILMU

40 µm per coat

TEORETICKÁ SPOTŘEBA

8-12 m²/l/coat

PRAKTICKÁ SPOTŘEBA

Practical coverage depends on many factors such as porosity and roughness of the substrate. A normal application consists of two layers. Apply an extra layer to areas with high exposure such as window sills and eaves.

PŘÍPRAVA POVRCHU

The surface must be clean, dry and free of dust, dirt, grease, oil, wax, mould, glue residues, etc. Remove old non-adhering layers of paint. Clean the surface using ND14. Use AMW concentrate to remove algae and mould.

NÁVOD K POUŽITÍ

Mix carefully before use.

PODMÍNKY POUŽITÍ

> 10°C, < 85% R.H.

APLIKACE A ŘEDĚNÍ: ŠTĚTEC

Apply with brush with synthetic bristles.

APLIKACE A ŘEDĚNÍ: VÁLEČEK

Apply with synthetic roller.

APLIKACE A ŘEDĚNÍ: BEZVZDUCHOVÝ SPREJ

Nozzle: 0.017 / Pressure: 140 - 170 bar

ČIŠTĚNÍ ZAŘÍZENÍ / ROZLITÍ

Use lukewarm soapy water to clean off stains and materials.

POZNÁMKY

Paracem® Universal is not recommended for use on floors, terraces, or horizontal surfaces that may be drenched in water or exposed to water for a long period of time. Before applying Paracem® Universal, we recommend that you thoroughly sand and degrease unweathered/new powder coatings and similar surfaces. Not suitable for application onto new plastisol or a new powder coating. These surfaces must be fully weathered. Paracem® Universal has no anti corrosive properties, so don't apply directly on ferrous metal surfaces, but always use an appropriate anticorrosive primer like Metal Cladding Primer. Specific substrates like enamelled bricks require an adhesion coat with diluted Noxyde.

DATA SAFETY DATA

Úroveň těkavých organických látek:	35 g/l
VOC readymix:	35 g/l
Kategorie VOC:	IIA/d
Limitní hodnota VOC:	130g/l (2010.)
Poznámky k bezpečnosti:	Consult Safety Data Sheet and Safety Information printed on the can.

DOBA POUŽITELNOSTI

Minimum of 2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5 and 35°C.

last_updated: 07/02/2025

footer_data_colors_pack_sizes: footer_data_colors_pack_sizes.value

footer_data_disclaimer: footer_data_disclaimer.value

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu