

Quality Paints since 1845  
**MATHYS**<sup>®</sup>



**PEGAFIX<sup>®</sup> UNIVERSAL**

## **Colourless impregnating primer**

High fixing capacity.

[WWW.MATHYSPAINTS.EU](http://WWW.MATHYSPAINTS.EU)



# PEGAFIX® UNIVERSAL

## POPIS PRODUKTU (DLHÝ)

Colourless impregnating primer based on acrylic hydrosols.

## ODPORÚČANÉ POUŽITIE

On different porous and chalking substrates, before painting them with waterborne paints.

## TECHNICAL DATA

|                                  |               |
|----------------------------------|---------------|
| Hustota (g/cm <sup>3</sup> ):    | 1,0           |
| Úroveň lesku:                    | Gloss         |
| Úroveň lesku pri 60°:            | Glossy: > 80% |
| Obsah pevných látok v hmotnosti: | 14 - 16 %     |
| Obsah pevných látok v objeme:    | 14 - 16 %     |

## DRY TIMES BY 20

|                               |           |
|-------------------------------|-----------|
| Na dotyk suché:               | 1 hour    |
| Suché na manipuláciu:         | 4 hours   |
| Suchý na opätovné natieranie: | 2-4 hours |
| Úplne vytvrdnuté:             | 24 hours  |

## ODPORÚČANÁ HRúbKA MOKRÉHO FILMU

100 µm

## ODPORÚČANÁ HRúbKA SUCHÉHO FILMU

15 µm

## TEORETICKÁ SPOTREBA

Very porous substrates (concrete, bricks): 5 - 10 m<sup>2</sup>/l  
Little porous substrates (plaster, porous paints for inside use): 15 - 20 m<sup>2</sup>/l

## PRAKTICKÁ VÝDATNOSŤ

Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

## PRÍPRAVA POVRCHU

Remove dust and / or clean carefully.  
Blistering plaster has to be sanded slightly to ensure a good adhesion or an adhesion test has to be done in advance.

## NÁVOD NA POUŽITIE

To ensure homogeneity, coating materials should be thoroughly stirred prior to use.

## PODMIENKY APLIKÁCIE

> 5°C, < 90% R.H.

## APLIKÁCIA A RIEDENIE: ŠTETEC

Apply undiluted.

## APLIKÁCIA A RIEDENIE: VALEC

Apply undiluted.

## APLIKÁCIA A RIEDENIE: BEZVZDUCHOVÉ STRIEKANIE

Nozzle: 11 - 15 / Pressure: 200 bars.  
Apply undiluted.

## APLIKÁCIA A RIEDENIE: VZDUCHOVO ATOMIZOVANÝ SPREJ

Apply undiluted.

## ČISTENIE ZARIADENIA / POSTRIEKANIE

Water.

## POZNÁMKY

On low porosity substrates, Pegafix is preferred above Parafix and Porisol because of its better penetration characteristics.  
Possible dried spots (on windows, floors, etc.) can be removed with Thinner 22.  
When using on chalking substrates, always test for fixing suitability.

## DATA SAFETY DATA

|                         |  |
|-------------------------|--|
| Úroveň VOC:             | 0 g/l  |
| VOC readymix:           | 0 g/l  |
| Kategória VOC:          | A/g  |
| Limit VOC:              | 30 g/l   |
| Poznámky k bezpečnosti: | Consult Safety Data Sheet and Safety Information printed on the can. |

## SKLADOVATEĽNOSŤ

Minimum of 2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

last\_updated: 07/02/2025

footer\_data\_colors\_pack\_sizes: footer\_data\_colors\_pack\_sizes.value

footer\_data\_disclaimer: footer\_data\_disclaimer.value

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
info@rust-oleum.eu

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
info@rust-oleum.eu

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
info@rust-oleum.eu

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
info@rust-oleum.eu