



Quality Paints since 1845
MATHYS®



PEGAPRIM® EXTERIOR

Water-based primer

- Reinforces the substrate and reduces absorption
- Neutralises differences in absorption characteristics
- Prevents differences in the glossiness of the topcoat
- Very good hiding characteristics
- Improves topcoat adhesion

PEGAPRIM® EXTERIOR

POPIS PRODUKTU (DLOUHÝ)

Water-based primer based on acrylic dispersions. Neutralises differences in the absorption characteristics of the substrate. Provides a substrate with uniform absorption and colour.

DOPORUČENÉ POUŽITÍ

Acrylate primer for exterior applications. Can be applied to most mineral substrates

TECHNICAL_DATA

Hustota (g/cm ³):	± 1,35 (weiss)
Úroveň lesku:	Matt
Úroveň lesku při 60°:	Matt: ± 5%
Obsah pevných látek v hmotnosti:	58 % (weiss)
Obsah pevných látek v objemu:	45 % (weiss)

DRY_TIMES_BY_20

Dotykem suché:	1,5 hours
Suchý nátěr:	2-3 hours
Plně vytvrzené:	1 week

DOPORUČENÁ TLOUŠŤKA MOKRÉHO FILMU

100 µm

DOPORUČENÁ TLOUŠŤKA SUCHÉHO FILMU

45 µm

TEORETICKÁ SPOTŘEBA

± 8 - 10 m²/l

PRAKTICKÁ SPOTŘEBA

Depends on several factors such as porosity and roughness of the substrate and material losses during application (see DIN 53220).

PŘÍPRAVA POVRCHU

The substrate should be dry, clean and free of grease. Pegaprim Exterior may be directly applied over normally porous substrates and old, cleaned paint layers if they are in good condition. Not suitable for highly porous substrates; use Pegafix as a fixator in such cases.

NÁVOD K POUŽITÍ

The product should be thoroughly stirred before use, to ensure homogeneity.

PODMÍNKY POUŽITÍ

> 5°C, < 80% R.H.

APLIKACE A ŘEDĚNÍ: ŠTĚTEC

Use undiluted.

APLIKACE A ŘEDĚNÍ: VÁLEČEK

Use undiluted.

APLIKACE A ŘEDĚNÍ: BEZVZDUCHOVÝ SPREJ

Nozzle: 011 - 015 / Pressure: 180 - 200 bar.

Apply undiluted.

APLIKACE A ŘEDĚNÍ: VZDUCHOVÝ ATOMIZOVANÝ SPREJ

Use undiluted.

ČIŠTĚNÍ ZAŘÍZENÍ / ROZLITÍ

Water.

DATA SAFETY DATA

Úroveň těkavých organických látek:	30 g/l
VOC readymix:	30 g/l
Kategorie VOC:	A/g
Limitní hodnota VOC:	30 g/l
Poznámky k bezpečnosti:	Refer to the Product Data Sheet and the information on the packaging.

DOBA POUŽITELNOSTI

At least 2 years from manufacturing date, if stored in the unopened, original packaging in dry, well-ventilated areas, not in direct sunlight, and at temperatures between 5° and 35°C.

last_updated: 07/02/2025

footer_data_colors_pack_sizes: footer_data_colors_pack_sizes.value

footer_data_disclaimer: footer_data_disclaimer.value

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu