

Quality Paints since 1845
MATHYS[®]



PORISOL[®]

Pore-filler

- Fixing
- Isolating
- Nearly odorless
- Can be recoated with water dispersed and most synthetic paints

POPIS PRODUKTU (DLOUHÝ)

Waterborn impregnating agent.

DOPORUČENÉ POUŽITÍ

As a pore-filler (inside): undiluted on very porous substrates (cardboard, paper, light kinds of woods), diluted on substrates with different absorption capacity (plaster, wood-fibre boards, etc.)

As a sealer (inside): undiluted on exotic wood, aniline colours and surfaces soiled with coaltar. Do not apply on substrates soiled with fume residues or soot (isolate first with Pegamat)

TECHNICAL DATA

Hustota (g/cm ³):	1,03 - 1,06
Úroveň lesku:	Gloss
Obsah pevných látek v hmotnosti:	50 - 52 %
Obsah pevných látek v objemu:	48 - 50 %

DRY TIMES BY 20

Dotykem suché:	30 minutes
Suchý nátěr:	1 hour

DOPORUČENÁ TLOUŠŤKA MOKRÉHO FILMU

100 µm

DOPORUČENÁ TLOUŠŤKA SUCHÉHO FILMU

48 µm

TEORETICKÁ SPOTŘEBA

3 - 10 m²/l per coat

PRAKTICKÁ SPOTŘEBA

Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

PŘÍPRAVA POVRCHU

The surfaces to be treated must be sound and dry. Remove non adhering parts (by scraping and rubbing), dust off carefully and degrease, if necessary.

APLIKACE A ŘEDĚNÍ: ŠTĚTEC

If necessary dilute with water.

APLIKACE A ŘEDĚNÍ: VÁLEČEK

If necessary dilute with water.

ČIŠTĚNÍ ZAŘÍZENÍ / ROZLITÍ

Water.

POZNÁMKY

When used as an impregnating agent, dilute 1/1 with water on substrates soiled with fume residue or soot, use Pegamat instead of Porisol.

DATA SAFETY DATA

Úroveň těkavých organických

látek: 0 g/l

VOC readymix: 0 g/l

Kategorie VOC: A/g

Limitní hodnota VOC: 30 g/l

Poznámky k bezpečnosti: Consult Safety Data Sheet and Safety Information printed on the can.

DOBA POUŽITELNOSTI

Minimum of 2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

last updated: 07/02/2025

footer_data_colors_pack_sizes: footer_data_colors_pack_sizes.value

footer_data_disclaimer: footer_data_disclaimer.value

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu