

Quality Paints since 1845
MATHYS[®]



PORISOL[®]

Pore-filler

- Fixing
- Isolating
- Nearly odorless
- Can be recoated with water dispersed and most synthetic paints

POPIS PRODUKTU (DLHÝ)

Waterborn impregnating agent.

ODPORÚČANÉ POUŽITIE

As a pore-filler (inside): undiluted on very porous substrates (cardboard, paper, light kinds of woods), diluted on substrates with different absorption capacity (plaster, wood-fibre boards, etc.)

As a sealer (inside): undiluted on exotic wood, aniline colours and surfaces soiled with coaltar. Do not apply on substrates soiled with fume residues or soot (isolate first with Pegamat)

TECHNICAL_DATA

Hustota (g/cm ³):	1,03 - 1,06
Úroveň lesku:	Gloss
Obsah pevných látok v hmotnosti:	50 - 52 %
Obsah pevných látok v objeme:	48 - 50 %

DRY_TIMES_BY_20

Na dotyk suché:	30 minutes
Suchý na opätovné natieranie:	1 hour

ODPORÚČANÁ HRúbKA MOKRÉHO FILMU

100 µm

ODPORÚČANÁ HRúbKA SUCHÉHO FILMU

48 µm

TEORETICKÁ SPOTREBA

3 - 10 m²/l per coat

PRAKTICKÁ VÝDATNOSŤ

Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

PRÍPRAVA POVRCHU

The surfaces to be treated must be sound and dry. Remove non adhering parts (by scraping and rubbing), dust off carefully and degrease, if necessary.

APLIKÁCIA A RIEDENIE: ŠTETEC

If necessary dilute with water.

APLIKÁCIA A RIEDENIE: VALEC

If necessary dilute with water.

ČISTENIE ZARIADENIA / POSTRIEKANIE

Water.

POZNÁMKY

When used as an impregnating agent, dilute 1/1 with water on substrates soiled with fume residue or soot, use Pegamat instead of Porisol.

DATA_SAFETY_DATA

Úroveň VOC:	0 g/l
VOC readymix:	0 g/l
Kategória VOC:	A/g
Limit VOC:	30 g/l
Poznámky k bezpečnosti:	Consult Safety Data Sheet and Safety Information printed on the can.

SKLADOVATEĽNOSŤ

Minimum of 2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

last_updated: 07/02/2025

footer_data_colors_pack_sizes: footer_data_colors_pack_sizes.value

footer_data_disclaimer: footer_data_disclaimer.value

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu